

Commercial Compact Desalinator





Commercial Compact Desalinator Features/Technical Information

- Available in 120L/hr and 185L/hr capacity
- Continuously rated
- Stainless steel powder coated frame
- Stainless steel CAT high pressure pump with pulsation dampener
- Freshwater flow meter & test port
- TDS meter to indicate potable water quality
- Stainless steel high & low pressure switches
- Multi-Media pre-filtration
- Two stage sediment pre-filtration
- Clear filter housings for easy filter inspection
- Filmtec membranes
- Hour meter for service intervals
- Membrane freshwater flush
- Frame dimensions 700w x 440h x 425d
- Overall dimensions 1200w x 530h x 425d
- Approx weight 68kg
- Available in single and three phase
- Approx operating current 9.5 Amps
- 12 Months limited warranty
- Valves for cleaning

Equipment supplied

- Feed pump (bronze)
- Multi-media filter (complete) and media
- 4 x sediment filters
- 1 x storage chemical
- Fittings & hose clamps for installation. (Hoses additional)
- Operating manual
- Sea water inlet non return valve



Commercial multimedia filter



- Overall height 1390 mm
- Width 480 mm
- Vessel width 250 mm
- Loaded dry weight 53 kg
- All fittings, pressure gage, flow controller supplied & fitted.